




H-9438 (SafeCombat Pro)

Tactical Design Work Boots (YKK Zip Design)



Upper : Full Grain Smooth Cow Leather+YKK™ Zip

Lining : BactiVOID™ Breathable Sandwich Air Mesh

Insole : Super Memory Foam Insoles

Outsole : QuantumHold™ PU/Nitrile Rubber Injection

Toecap : VortiGard™ Steel Toecap

Penetration : VortiGard™ Steel Midsole Plate

Size : EU 37-47#, UK 3-13#, US4-14#

CE EN ISO 20345:2022 S3 SR HRO

ASTM E 2149-2020 Approved Anti-bacteria Lining & Insole (Odor Resistant)

Application : Construction, Logistics, Mechanics, Factory Workshop, Airport, Military, Police, Guarders etc



VortiGard™ Steel Toecap Protection • EN ISO 20345:2022

Stainless Steel Toecap is heavy duty and corrosion resistant. The impact resistance can reach 200 joules from falling or rolling objects. The compression resistance can reach 15kN.



VortiGard™ Steel Plate Protection • EN ISO 20345:2022

Steel midsole plate is flexible and corrosion resistant. The penetration resistance can reach 1100 newtons from nail or other sharp objects. The flex resistance can reach to 1 X 10⁶ flexion cycles without visible cracking.



LeatherQua™ Cow Leather Upper • EN ISO 20345:2022

High quality full grain smooth cow leather with thickness 1.6-1.8mm. It is treated with water resistant coating to keep feet dry from raining workday. The tear strength of upper leather can reach to 120 Newtons.




QuantumHold™ PU/Rubber Outsole • EN ISO 20345:2022

The outsole is made with PU/Nitrile Rubber material. The midsole is 45±5 degree hardness PU, which is soft and shock absorption. The outsole is natural rubber with 5%-10% nitrile, which is abrasion resistant, slip resistant, oil resistant and heat resistant.

Sole Bonding Strength Test

- EN ISO 20345:2022 (Between Upper & Sole)
- Average Test Result 5.8 ± 5 (N/mm)



Upper, Lining & Bonding Strength Test Result

| | |
|-----------------------------------|------------------------|
| Leather Tear Strength \geq | 120.0 Newtons |
| Leather Tensile Properties \geq | 15.0 N/mm ² |
| Lining Tear Strength \geq | 15.0 N/mm |
| Bonding Strength \geq | 4.0 N/mm |

| ✓ Protection With Slip Resistant (SR) | | Result |
|--|--|--|
| Test Requirement : Forward Heel Slip ≥ 0.31 (ISO 13287:2019) Backward Heel Slip ≥ 0.36 (ISO 13287:2019) | | PASS |
| Standards : EN ISO 20342:2022(5.3.5) , Test floor: Ceramic tile, Lubricant: Sodium lauryl sulphate | | |
| ✓ Protection With Anti-Static | | Result |
| Test Requirement : Anti-static 100K Ω -1000M Ω , Test Voltage: 100 \pm 2 V DC, Test Period: 1 Minute | | PASS |
| Standards : EN ISO 20345:2022 (6.2.2.2) Dry Humidity (30 \pm 5) & Wet Humidity (85 \pm 5) | | |
| ✓ Protection Resistant to Fuel Oil | | Result |
| Test Requirement : Change in Volume and Change in Hardness (Outsole) is No More Than +12%(*) | | PASS |
| Standards : EN ISO 20345:2022 (6.4.2) | | |
| SAFETOE Standard Package Instruction (Average 42# for Reference) | | |
| Shoes Weight : 1.4-1.5 KGS /Pair | | Carton Weight : 15-16 KGS /Carton |
| 1 Pair / Color Box , Dimensions : 32 \times 28 \times 12CM | | 10 Pair / Carton , Dimensions : 62 \times 57 \times 33CM |



User Instructions:

- 1.) RECOMMENDED TO USE : Construction, Logistics, Mechanics, Glasses Installation, Factory Workshop, Farming, Garden, Garage etc.
- 2.) LIMITATION TO USE: It is very important that footwear selected must be suitable for the right workplaces. The protection against risks or hazards which are not mentioned in this document is not warranted.
- 3.) FITTING & SIZE: All footwear are marked with standard size on tongue label. Some are with different size comparison, such as EU size, UK size, US size etc. Please wear footwear in a suitable size.

Footwear which are too loose or too tight may not provide optimum level of protection.

4.) STORAGE: Keep the footwear in its original packaging, under ordinary temperature, non-humidity conditions and in clean, covered and ventilated premises.

5.) CLEANING: Clean footwear regularly by high quality cleaning treatments recommended as suitable for the purpose. Don't use caustic or corrosive cleaning agents.