

Industrial Chelsea Safety Boots

Model: M-8025 | SlidGuard






					
Toe Cap Protection	Anti Penetration	Slip Resistance	Anti Static	Shock Absorption	Antibacterial

Technical Specifications




Upper	Smooth Cow Leather
Lining	Bactivoi [™] Breathable Sandwich Mesh
Insole	Anti-Fatigue Memory Foam Insole
Outsole	PU/PU Dual-Density Outsole
Toe Cap	VortiGard [™] Steel Toe Cap (200J)
Midsole	VortiGard [™] Steel Midsole (1100N)
Size Range	EU 37–47 UK 3–13 US 4–14
Weight	Approx. 650g / shoe (EU42)

Certifications & Standards







	EN ISO 20345:2022+A1:2024 S3 SR FO
	ASTM F2413-24 I/C PR SD100
	CSA Z195:14

Performance Notes

- **SR:** Slip Resistance Tested on Ceramic Tile with Glycerol
- **FO:** Fuel Oil Resistant Outsole
- **E:** Energy Absorption of Seat Region
- **Anti-Static:** Electrical Resistance 100kΩ–1000MΩ

		
VortiGard[™] Steel Toe Cap (200J) Maximum Impact Protection from Falling or Rolling Objects.	VortiGard[™] Steel Midsole (1100N) Maximum Penetration Protection Against Sharp Objects	Slip-Resistant & Durable Outsole Excellent Grip, Wear Resistance and Oil Resistance

Recommended Applications:

					
Construction	Manufacturing	Heavy Industry	General Maintenance	Light Industry	Outdoor Work



Scan for More Information

www.safetoe.net