

Industrial Chelsea Safety Boots

Model: M-8025 | SlidGuard



**Toe Cap
Protection**



**Anti
Penetration**



**Slip
Resistance**



Anti Static



**Shock
Absorption**



Antibacterial

Technical Specifications

Upper	Smooth Cow Leather
Lining	Bactivoi [™] Breathable Sandwich Mesh
Insole	Anti-Fatigue Memory Foam Insole
Outsole	PU/PU Dual-Density Outsole
Toe Cap	VortiGard [™] Steel Toe Cap (200J)
Midsole	FlexBarrier [™] Steel Midsole (1100N)
Size Range	EU 37–47 UK 3–13 US 4–14
Weight	Approx. 650g / shoe (EU42)

Certifications & Standards


	EN ISO 20345:2022+A1:2024 S3 SR FO
	ASTM F2413-24 I/C PR SD100
	CSA Z195:14

Performance Notes

- **SR:** Slip Resistance Tested on Ceramic Tile with Glycerol
- **FO:** Fuel Oil Resistant Outsole
- **E:** Energy Absorption of Seat Region
- **Anti-Static:** Electrical Resistance 100kΩ–1000MΩ



VortiGard[™] Steel Toe Cap (200J)
Maximum Impact Protection
from Falling or Rolling Objects.



FlexBarrier[™] Steel Midsole (1100N)
Maximum Penetration Protection
Against Sharp Objects



Bactivoi[™] Comfort Lining
Enhanced Comfort and
Moisture Management.

Recommended Applications:



Construction



Manufacturing



Warehousing



General
Maintenance



Light
Industry



Outdoor
Work



Scan for
More Information

www.safetoe.net