



**safetoe**  
TOP QUALITY SINCE 1984

Top Quality  
Creative Design  
Amazing Comfort



Keep Worker in Safe!

# M-8356RB VoltGuarder

## 18kV EH Rated Dielectric Work Boots



Electric Hazard 18KV



Upper : Full Grain Smooth Cow Leather

Lining : Breathable Sandwich Mesh

Insole : Super Memory Foam Insoles

Outsole : PU/Nitrile Rubber Injection (Slip Resistant)

Toecap : Composite Toecap

Penetration : Kevlar Midsole Plate

Size : EU 37-47#, UK 3-13#, USA-14#

CE EN ISO 20345:2022+A1:2024 SBP+I SR CI HI FO HRO

ASTM F2413-18 M I/75 C/75 PR EH

ASTM E 2149-2020 Approved Anti-microbial Lining & Insoles (Odor Resistant)

Application : Energy Power Plansts, Electric Transformer, Tel-Communication, Household Appliance Electrician etc



200 JOULE TOECAP



SLIP-RESISTANT



SHOCK ABSORPTION



ELECTRIC HAZARD 18KV



ANTI-NAIL MIDSOLE



PETROL AND CHEMICAL RESISTANT



WATER RESISTANT



OIL RESISTANT



### Composite Toe Cap Protection • EN ISO 20345:2022

Compoiste Toecap is light-weight and non-magnetic. The impact resistance can reach 200 joules from falling or rolling objects. The compression resistance can reach 1500kN.



### Kevlar Plate Protection (Type PS) • EN ISO 20345:2022

Kevlar midsole plate is flexible and non-metallic. The penetration resistance can reach 1100 newtons from nail or other sharp objects. The flex resistance can reach to  $1 \times 10^6$  flexion cycles without visable cracking.



### Water Resistant Cow Leather Upper • EN ISO 20345:2022

High quality full grain smooth cow leather with thickness 1.6-1.8mm. It is treated with water resistant coating to protect feet from raining workday. The tear strength of upper leather can reach to 120 Newtons.



### Heavy Duty PU/Rubber Outsole • EN ISO 20345:2022

PU/Rubber outsoules are manufacturerd with Germany Fully Automatic Injection Technology. The midsole is  $45 \pm 5$  degree hardness PU, which is soft and shock absorption. The outsole is natural rubber with 5%-10% nitrile, which is abrasion resistant, slip resistant, oil resistant and heat resistant.

## Sole Bonding Strength Test

- EN ISO 20345:2022, 5.3 (Between Upper & Sole)
- Average Test Result  $5.8 \pm 5$  (N/mm)



### Upper, Lining & Bonding Strength Test Result

Leather Tear Strength $\geq$	120.0 Newtons
Leather Tensile Properties $\geq$	15.0 N/mm <sup>2</sup>
Lining Tear Strength $\geq$	15.0 N/mm
Bonding Strength $\geq$	4.0 N/mm

### ✓ Protection Against Electric Hazard (EH 18KV)

### Result

Test Requirement : Test Voltage 18KV, Test Period 1 Minute, Leakage Current  $\leq$  1.0mA

PASS

Standards : ASTM F2412-18a, Clause 9

### ✓ Protection With Slip Resistant (SR)

### Result

Test Requirement : Forward Heel Slip  $\geq$ 0.31 ( Test methodL ISO 13287:2019)

Backward Forepart Slip  $\geq$ 0.36 ( Test methodL ISO 13287:2019)

PASS

Standards : EN ISO 20345:2022(5.3.5) , Test floor: Ceramic tile, Lubricant: Sodium lauryl sulphate

### ✓ Protection Resistant to Fuel Oil (FO)

### Result

Test Requirement : Change in Volume and Change in Hardness (Outsole) is No More Than +12%(\*)

PASS

Standards : EN ISO 20345:2022 (6.4.2)

### SAFETOE Standard Package Instruction (Average 42# for Reference)

Shoes Weight : 1.2-1.3 KGS /Pair

Carton Weight : 13-14 KGS /Carton

1 Pair / Color Box , Dimensions : 32×24×12CM

10 Pair / Carton , Dimensions : 62×49×33CM



### User Instructions:

- 1.) RECOMMENDED TO USE : Energy Power Plants, Electric Transformer, Tel Communication, Household Appliance Electrician etc.
- 2.) LIMITATION TO USE: It is very important that footwear selected must be suitable for the right workplaces. The protection against risks or hazards which are not mentioned in this document is not warranted.
- 3.) FITTING & SIZE: All footwear are marked with standard size on tongue label. Some are with different size comparison, such as EU size, UK size, US size etc. Please wear footwear in a suitable size.

Footwear which are too loose or too tight may not provide optimum level of protection.

4.) STORAGE: Keep the footwear in its original packaging, under ordinary temperature, non-humidity conditions and in clean, covered and ventilated premises.

5.) CLEANING: Clean footwear regularly by high quality cleaning treatments recommended as suitable for the purpose. Don't use caustic or corrosive cleaning agents.